



DWV

uPVC SANITARY PIPING SYSTEM



ATLANTA INDUSTRIES, INC.

est. 1978



Ver. 03 October 2015

APPLICATION:

ATLANTA DWV sanitary pipe is designed for above and underground sanitary piping system. It is ideal for drain, waste and vent installation. Approved by contractors, architects, engineers and private home-owners. Conforms with ASTM D 2729 specification.

PIPE SPECIFICATION:



ADVANTAGES :

- High-Impact Resistance
- Non-Corrosive
- Lightweight
- High Chemical Resistance
- Smooth Internal Pipe Surface

COLOR : ORANGE

MATERIAL : POLYVINYL CHLORIDE



NOMINAL SIZE		OUTSIDE DIAMETER	WALL THICKNESS (T)		LENGTH (L) MM
MM	INCH		S 600	S 1000	
63	2	57.15	1.9	2.54	3000
90	3	82.55	2.5	3.70	3000
110	4	107.10	2.5	3.80	3000



FITTING RANGE

ELBOW 90°	ELBOW 45°	TEE	WYE	CLEAN OUT SET
2 3 4	2 3 4	2 3 4	2 3 4	2 3 4
COUPLING	P-TRAP W/ PLUG	DOUBLE WYE <small>note: made to order</small>	DOUBLE TEE <small>note: made to order</small>	WYE REDUCER
2 3 4	2 3 4	2 3 4	2 3 4	3 x 2 4 x 2 4 x 3
DOUBLE WYE REDUCER	TEE REDUCER	DOUBLE TEE REDUCER <small>note: made to order</small>	TAP TEE	BUSHING REDUCER
3 x 2 4 x 2 4 x 3	3 x 2 4 x 2 4 x 3	3 x 2 4 x 2 4 x 3	2 x 1 1/2 3 x 1 1/4	3 x 2 4 x 2 4 x 3

INSTALLATION PROCEDURE

1. Cut the pipe square using a hand saw or a PVC pipe cutter.
2. Remove all burrs, dirt and oils before applying solvent cement.
3. Apply solvent cement evenly to spigot & slightly thicker layer to the inside of the socket.
4. Insert the pipe into the fitting, apply 1/4 twist & hold for at least 10 seconds to prevent the pipe from pulling back.
5. Wipe off excess solvent cement.
6. For better jointing use Atlanta PVC solvent cement.



Unit 35th Atlanta Centre, #31 Annapolis St., Greenhills, San Juan City
Tel. nos.: 723.0781 to 96 | 744.4700 Fax no.: 722.8705 | 723.9576

Website: <http://www.atlanta.ph>
Email: marketing@atlanta.ph
Like us on Facebook [atlantaindustriesinc](#)